

Adjustable Base

SHB 06



Model	SHB06	SHB12	SHB20	SHB30	SHB50	SHB100
Load Cap. (MT)	0.6	1.2	2	3	5	10
Max. rotation torque (Nm)	900	2400	4000	6000	10000	20000
Eccentricity (mm)	150	200	200	200	200	200
Rotation speed (rpm)	0.05-2	0.03-1.2	0.03-1.2	0.025-1.0	0.02-0.8	0.012-0.48
Max. tilt torque (Nm)	1800	3600	6000	9000	15000	40000
Centre of gravity (mm)	300	300	300	300	300	400
Tilt speed (rpm)	0.35	0.35	0.35	0.35	0.2	0.2
Tilt range(°)	0-135	0-135	0-135	0-130	0-130	0-130
Table diameter (mm)	800	900	1100	1300	1500	2000
Number of T slots and width (mm)	4×14	4×20	4×20	4×22	6×22	6×26
Inherent overhang (mm)	150	160	160	180	200	230
Table height from the floor (mm)	Min 850 Max 1300	Min 1000 Max 1450	Min 1100 Max 1550	Min 1200 Max 1800	Min 1300 Max 2050	Min 1450 Max 2200
Manually adjustable increments(mm)	150	150	150	150	150	150
Max. welding current (A)	500	500	500	700	1000	1000
Power supply	AC 415-3P,50Hz					

SHB 1.2



Model	SHB10	SHB20	SHB40	SHB60
Capacity(Kg)	1000	2000	4000	6000
Elevating height (mm)	Max	1420	1700	1800
	Min	920	1100	1200
Table Dia. (mm)	900	1100	1400	1500
Table Rev. speed(rpm)	0.12-1.2	0.06-0.5	0.06-0.5	0.06-0.5
Max eccentric(mm)	150	120	120	120
Rev. Motor power(kW)	1.1	1.1	1.5	2.2
Max Gravity(mm)	350	300	300	300
Turning motor power(kW)	1.1	1.5	2.2	3
Turning degree(°)	0-135°	0-135°	0-135°	0-135°
Speed mode	Rev.	By inverter		
	Turning	Fixed		

SHB20m Power Height Adjustable



Model	SHB20M
Max. loading capacity (Kg)	2000
Max. eccentricity (mm)	200
Max. Centre of gravity (mm)	300
Table size (mm) D	1200
Rotation speed(rpm)	0.1-1.0
Tilt speed (rpm)	0.33
Tile angle (°)	135
Lift speed (mm/min)	780
Lift stroke(mm)	500
Overall table height(mm)	1090-1590
Welding current(amps)	500
Price USD	8,000/set (without chuck)